High Ambient 50 Hz Split Air Conditioners

The Flair split air conditioner line is designed with numerous energy efficiency, health and well-being features. The Eco Smart mode adjusts the temperature while you are away from home or sleeping to save energy and money. The Peak Efficiency heat exchanger, with a curved design, greatly improves cooling/heating performance. The My Temp Remote Sensor uses a sensor in the remote control. rather than in the evaporator high on the wall, for cooling or heating to the temperature you selected. The Turbo feature quickly cools or heats the room with the touch of a button. The evaporator has an auto clean option that, with the touch of a button, prevents the formation of mold and mildew by running the fan after the air conditioner is turned off.



FEATURES

R22 Refrigerant

Reciprocating High Ambient Compressor

Evaporator Electronic Display

LCD Wireless Remote Control

Automatic Swing Louvers

24 Hour On/Off Timer

Auto-Restart

Eco Smart Mode

Auto Clean Evapoartor

My Temp Remote Sensor

Turbo Function *

4 Fan Settings (High, Medium, Low and Auto)

Quiet Operation

Weather Resistant Condenser Cabinet

Dehumidification Function

Bio/HEPA Filter

Removable Active Carbon & Nylon Filter

Safety Lock

Peak Efficiency Heat Exchanger

Heat Pump / Cool Models

Easy Installation

Available in White

* Feature not available on 28K BTU models

Special Note: the 28K BTU model has a similar design

but has partial width discharge louvers.







Electrolux Major Appliances Intl 10200 David Taylor Drive, Charlotte, NC 28262 USA www.philco-intl.com

Philco is a registered trademark of Electrolux Home Products, Inc. 2012

Split Air Conditioners Specifications

MODELS	PAHC18GNBWM	PAHP18GNBWM
Voltage / Hertz	220-240 / 50	220-240 / 50
Type	Cooling Only	Heat Pump
BTU/Hr (cool/heat)	17400	18000 / 18800
SYSTEM FEATURES	17 100	100007 10000
Amps (cool/heat)	8.32	8.32 / 8.11
Watts (cool/heat)	1877	1875 / 1827
Energy Class (EER / COP)	C, UAE 5 Star	C/C
Refrigerant	R22	R22
Compressor Type	Reciprocating High Ambient	Reciprocating High Ambient
Dehumidification (L/pints per hr)	1.8 / 3.8	1.8 / 3.8
Connection Pipe Liquid (mm/in)	6.35 / .25	6.35 / .25
Connection Pipe Gas (mm/in)	16.0 / .63	16.0 / .63
Approvals	IEC / RoHS	IEC / RoHS
Color	White	White
EVAPORATOR DIMENSIONS & WEIGHT		
HeightxWidthxDepth (mm)	299 x 945 x 209	299 x 945 x 209
Net Weight (kg/ l b)	12.0 / 26.4	12.0 / 26.4
CONDENSER DIMENSIONS & WEIGHT		
HeightxWidthxDepth (mm)	700 x 1018 x 412	700 x 1018 x 412
Net Weight (kg/ l b)	59.0 / 129.8	62.0 / 136.4
CONTAINER LOADING		
20'/40'/40'HC without tubing kits	57 / 120 / 132	57 / 120 / 132

MODELS	PAHP24GNBWM	PAHC28GNBWM
Voltage / Hertz	220-240 / 50	220-240 / 50
Type	Heat Pump	Cooling Only
BTU/Hr (cool/heat)	23000 / 25010	27100
SYSTEM FEATURES		
Amps (cool/heat)	10.65 / 10.80	13.94
Watts (cool/heat)	2400 / 2435	3142
Energy Class (EER / COP)	C/C	D, UAE 3 Star
Refrigerant	R22	R22
Compressor Type	Reciprocating High Ambient	Reciprocating High Ambient
Dehumidification (L/pints per hr)	2.4 / 5.1	3.0 / 6.3
Connection Pipe Liquid (mm/in)	6.35 / .25	6.35 / .25
Connection Pipe Gas (mm/in)	16.0 / .63	16.0 / .63
Approvals	IEC / RoHS	IEC / RoHS
Color	White	White
EVAPORATOR DIMENSIONS & WEIGHT		
HeightxWidthxDepth (mm)	315 x 1018 x 230	326 x 1 17 8 x 252
Net Weight (kg/lb)	15.0 / 33.0	18.0 / 39.6
CONDENSER DIMENSIONS & WEIGHT		
HeightxWidthxDepth (mm)	700 x 1018 x 412	840 x 1018 x 412
Net Weight (kg/lb)	69.0 / 151.8	73.0 / 160.6
CONTAINER LOADING		
	56 / 115 / 131	36 / 76 / 90



Electrolux Major Appliances Intl 10200 David Taylor Drive, Charlotte, NC 28262 USA www.philco-intl.com

 $Phil co is a registered \, trademark \, of \, Electrolux \, Home \, Products, \, Inc. \, \, 2012 \,$